

# IvedaXpress™ Enabled IP Camera



Cloud  
Ready

**Z-3510**

(powered by Iveda Cloud)



- Easy to set up
- Excellent video quality at an affordable price
- See all your cameras on a single dashboard
- View from your computer, tablet or smartphone
- Cloud hosted, 24/7 Web access to live & recorded video



**IvedaXpress**



Zee™ cameras are enabled for IvedaXpress™ cloud-managed video hosting service. These are inexpensive, plug and play IP cameras. Especially designed with consumers and small businesses in mind, IvedaXpress eliminates the many hours of network setup and upkeep. With IvedaXpress, Zee cameras in numerous locations may be accessed on one online dashboard on virtually any Internet-enabled smartphone, tablet or computer, wherever you are in the world. The solution provides an inexpensive and easy to install enterprise level video surveillance solution for home, office or business.



Address:  
2F.-15, No.14, Ln. 609, Sec. 5, Chongxin Rd.,  
Sanhong Dist., New Taipei City 241  
Phone: 02-29997699 Fax: 02-29997808  
Web: [www.iveda.com](http://www.iveda.com)

# Z-3510

## 攝影機

型號	Z-3510 2百萬畫數攝影機
感光元件	1/2.7" CMOS
鏡頭光圈	3.6mm 固定鏡頭, F1.8
最低照度	Black & White 0 Lux Color 0.01Lux@F1.2
紅外線射程	照射距離30-40公尺(meter)
日/夜間模式	ICR自動切換 · 低照時彩色轉黑白
電子快門	1/3 ~ 1/100,000秒

## 錄像

影像壓縮	H.265 / H.264 / MJPEG 提供主profile 和第二profile做切換
有效像素	1920(H) x 1080(V)
最高解析/張數	1920 x 1080 / 1280x720 (30張/秒)
影像串流	支援 H.265 / H.264 / MJPEG 支援單點傳播和多點傳送(RTSP)
影像設定	亮度、對比度、飽和度、銳利度、 背光補償、時間戳記、日夜模式、3D降噪功能

## 網路

安全性	用戶等級密碼保護
支援協定 (protocols)	HTTP, HTTPS, TCP, IP, UDP, DDNS, NTP, RTP, RTSP, FTP, SMTP
時間校正	具NTP校時功能 可網路時間同步、電腦同步、手動調整

## 警示和事件

警示和 事件管理	輸入: 移動偵測 輸出: FTP/SMTP/ HTTP/ 事件 HTTPS, 事件前後警示
-------------	---

## 系統

機殼材質	鋁合金: 機身和支架 玻璃和塑膠: 鏡頭保護罩
防水殼	IP66
連接埠	RJ45 Ethernet (10/100Base -T)
電力	12V DC, 1A / 耗電:7.5W(MAX) PoE (乙太網路供電) 符合 IEEE 802.3af type A
運作環境	工作溫度: -10~ 50 °C 濕度: <95%相對溼度(未凝結)
建議瀏覽	256MB RAM 顯示卡 (或同等級內建顯示卡)
建議規格	1G RAM Windows XP / 7 / 8 / 10, MAC OS, Linux
配件	安裝及相關套件
認證	CE
安裝/管理/維護	* 攝影機內建雲端系統連結韌體, 當攝影機接通 電源和網路, 會自行連結雲端即時影像監控平台 不需再做網路IP設定, 管理者即可綁定、刪除、 管理攝影機。若攝影機有與監控使用者帳號綁定 接通電源和網路後, 現場即時影像即自動回傳、 儲存至雲即時影像監控系統, 可從監控網頁端觀 看即時影像、回放和下載錄影檔。(儲存功能需 配合對應的硬體儲存設備) * 從遠端管理網頁切換攝影機畫素、基本攝影機 功能; 可檢視攝影機在線狀況。 * 管理者可以從遠端網頁連結到, 設定攝影機介 面, 登入後可調整: 亮度、銳利度、日夜模式。 * 支援從IE瀏覽器觀看 * 相機設定: 亮度, 清晰度, 日夜模式....

